

**USE OF PRODUCT**

The PRIME Architectural Recessed Multiple Series is offered in an assortment of lumen, color temperature, beam angle, and filter options that may be modified in the field. Modules are available in bevel, regress, or snoot appearance.

LED MODULE

Cree LEDs in 2700K, 3000K, 3500K, or 4000K in standard 93+ CRI. 2 Step MacAdam ellipse allows for color consistency between fixtures. LED mounted to aluminum heat sink for maximum life output and thermal management. LED module is field replaceable.

FRAME CONSTRUCTION

Constructed from 20 gauge cold rolled steel with powder coat finish.

ADJUSTMENT

0-35° Hot aiming.

OPTICS

Field replaceable TIR optics available in 18°, 30°, 50°, and 80°. Easily achieve narrow spot to wide flood beam pattern. Option for frosted, honeycomb, or solite filter (2 maximum).

DIMMING

Available in 7 driver selections. (ID) Standard all-inclusive ELV, Triac, and 0-10V dimming driver called Intelligent Drive, 120-277V. (PEQ0) Lutron Hi-Lume Premier Ecosystem 0.1% w/soft on, fade to black dimming, 120-277V. (LDE1) Lutron Hi-Lume 1% Ecosystem with soft on, fade to black dimming, 120-277V. (L3DA) Hi-lume 1% EcoSystem/3-Wire L3D Driver (EEI) eldoLED Eco 1% Dim (0-10V), 120-277V. (EDIO) eldoLED Solo 0.1% Dim(0-10V), 120-277V. (EDID) eldoLED Solo 0.1% Dim(DALI), 120-277V. All drivers are integral and are field replaceable.

THERMAL MANAGEMENT

Ambient temperatures at fixture location should not exceed -20° to 40°C.

MOUNTING

Butterfly brackets available to accommodate Adjustable bar hanger, C-channel bar hanger and Flat bar hanger.

LABELS/COMPLIANCE/WARRANTY

- CSA Listed for US and Canada
- 5 Year limited warranty

**ORDERING INFORMATION****RPM**

Family		Mounting types		Module Configuration		Module Size/Lumens		Dimming		Optical Lens		Filter		Trim Type	
Series	Aperture Type	Module Configuration		Lumen per head		Color Temperature		Voltage		Dimming		Optical Lens		Filter	
RPA3	OP - Open Bevel	1 - One module		8L - Medium module in 800 lm		27 - 2700K		UNV - 120-277V		ID ¹ - Standard all-inclusive ELV, Triac, and 0-10V dimming driver (Intelligent Drive)		18 - 18°		None - Leave blank	
Elevate Series		2 - Two module		11L - Medium module in 1175 lm		30 - 3000K		120 - 120V		PEQ0 - Lutron Hi-Lume Premier Ecosystem 0.1% w/soft on, fade to black dimming		30 - 30°		F - Frosted filter	
		3 - Three module		16L - Medium module in 1650 lm		35 - 3500K				LDE1 ² - Lutron Hi-Lume 1% Ecosystem with soft on, fade to black dimming		50 - 50°		H - Honey comb	
		MT0 - Made to order				40 - 4000K				L3DA - Hi-lume 1% EcoSystem/3-Wire L3D Driver		80 - 80°		S - Solite filter	
										EEI ² - eldoLED Eco 1% Dim (0-10V)					
										EDIO ^{2,3} - eldoLED Solo 0.1% Dim (0-10V)					
										EDID ^{2,3} - eldoLED Solo 0.1% Dim (DALI)					
Optical Lens		Filter		Housing Type		Aperture		Frame Accessories		Options					
18 - 18°		None - Leave blank		IC - IC Air-tight New Construction		SFA - Square Flange Adjustable		UH ⁴ - Universal bar hanger		EM - Emergency Battery					
30 - 30°		F - Frosted filter		ICP - IC New Const. Chicago Plenum				C - C-Channel bar hanger		LAW - Lutron Athena Wireless Node (RF only version)					
50 - 50°		H - Honey comb		NC - Non-IC Air-tight New Construction				B - Flat bar hanger							
80 - 80°		S - Solite filter													

TRIM ORDERING INFORMATION

Aperture Size / Shape / Trim Type / Style	Bevel Opening	Bevel	Flange	Options
3RFO - 3" Square Flange Open	CL - Die cast large opening	W - White B - Black BZ - Bronze MT0 - Made to order	W - White B - Black BZ - Bronze MT0 - Made to order	WL - Wet Location

- Notes
- Intelligent Drive is the standard driver.
 - Ceiling access required.
 - Must specify logarithmic or inear eldoLED driver.
 - Requires IC Housing