



USE OF PRODUCT

The Elevate Architectural Cable Series offers a point source solution that is available in a single gimbal with retractable yoke. Offered in an assortment of lumen, color temperature, beam angle, and filter options that may be modified in the field. Modules are available in bevel, regress, or snoot appearance. This product is for indoor use only.

LED MODULE

Cree LEDs in 2700K, 3000K, 3500K, or 4000K in standard 93+ CRI. 2 Step MacAdam ellipse allows for color consistency between fixtures. LED mounted to aluminum heat sink for maximum life output and thermal management. LED module is field replaceable.

FRAME CONSTRUCTION

Constructed from 20 gauge cold rolled steel with powder coat finish.

ADJUSTMENT

Single gimbal (45° Tilt) with retractable yoke and 360° rotation. Both mechanisms are lockable.

OPTICS

Field replaceable TIR optics available in 12°, 22°, 27°, 35°, and 45°. Easily achieve narrow spot to wide flood beam pattern. Option for frosted, honeycomb, or solite filter (2 maximum).

DIMMING

Available in 7 driver selections. (ID) Standard all-inclusive ELV, Triac, and 0-10V dimming driver called Intelligent Drive, 120-277V. (PEQ0) Lutron Hi-Lume Premier Ecosystem 0.1% w/soft on, fade to black dimming, 120-277V. (LDE1) Lutron Hi-Lume 1% Ecosystem with soft on, fade to black dimming, 120-277V. (L3DA) Hi-lume 1% EcoSystem/3-Wire L3D Driver (EEI) eldoLED Eco 1% Dim (0-10V), 120-277V. (EDIO) eldoLED Solo 0.1% Dim(0-10V), 120-277V. (EDID) eldoLED Solo 0.1% Dim(DALI), 120-277V. All drivers are integral and are field replaceable.

THERMAL MANAGEMENT

Ambient temperatures at fixture location should not exceed -20° to 40°C.

MOUNTING

Mounts directly to junction box.

LABELS/COMPLIANCE/WARRANTY

- CSA Listed for US and Canada
- Damp rated
- 5 Year limited warranty



ORDERING INFORMATION

RPM

Family Mounting types Module Configuration Lumens Per Head Color Temperature Optical Lens Voltage Dimming Optical Lens Filter Trim Type Frame Finish

Series	Housing Size	Mounting Types	Module Configuration	Lumens Per Head	Color Temperature	Voltage
RPM	M - Medium	C ¹ - Cable hung	1 - One module 2 - Two module 3 - Three module 4 - Four module 4S - Four module w/ Square Config. MTO - Made to order	8L - 890 lm 11L - 1175 lm 16L - 1650 lm 21L - 2100 lm	27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K	UNV - 120-277V 120 - 120V

Dimming	Optical Lens	Filter	Module Type	Frame Finish	Module Finish	Options
ID ² Standard all-inclusive ELV, Triac, and 0-10V dimming driver (Intelligent Drive)	12 - 12° 22 - 22° 27 - 27° 35 - 35° 45 - 45°	None - Leave blank F - Frosted filter H - Honeycomb S - Solite filter	R ⁶ - Regress B - Bevel S - Snoot	B - Black W - White S - Silver MTO - Made to order	B - Black W - White S - Silver MTO - Made to order	EM - Emergency Battery LAW - Lutron Athena Wireless Node (RF only version)
PEQ0 Lutron Hi-Lume Premier Ecosystem 0.1% w/ soft on, fade to black dimming						
LDE1 Lutron Hi-Lume 1% Ecosystem with soft on, fade to black dimming						
L3DA Hi-lume 1% EcoSystem/3-Wire L3D Driver						
EEI ^{4,5} eldoLED Eco 1% Dim (0-10V)						
EDIO ^{4,5} eldoLED Solo 0.1% Dim (0-10V)						
EDID ^{4,5} eldoLED Solo 0.1% Dim (DALI)						

1. 5ft standard cable length.
2. Intelligent Drive is the standard driver.
3. 120V only.
4. Must specify logarithmic or linear eldoLED driver.
5. Confirm dimming curve: linear or logarithmic.
6. Standard



LUMEN CHART

Wattage	Delivered Lumens	Voltage	CRI
10W	890 lm	120 - 277V	93+
14W	1175 lm	120 - 277V	93+
20W	1650 lm	120 - 277V	93+
30W	2100 lm	120 - 277V	93+



*Above chart, ordering information, and IES File name reflect delivered lumens based 3000K and 30° optical lens.
 **Lumens will vary based on CCT, optical lens, and bevel finish.

DIMENSION/CONFIGURATION



One module





Two module





Three module




Four module




Four module in Square config.





Module Mechanism



CABLE DIMENSION



Cable Hung Canopy



OPTICAL LENS




12°, 22°, 27°, 35°, 45°

FILTERS




H - Honey comb F - Frosted filter S - Solite filter


MODULE TYPE



R - Regress



B - Bevel



S - Snoot

3/64" Galvanized Cable Fuse Cut with Die Cast #1 Stop
 Available in 24", 36", 50", 72", 100", 120", & 150" Lengths
 7x7 Cable - MAX LOAD 270 lbs